


### Flexible Circular Copper Braid Bonds



**Flexible Circular Copper Braid Bonds** are terminated with cable lugs at each end. Use to bond gates, doors, fences etc.

| BRAID DIA. (mm) | LENGTH (B) (mm) | HOLE DIA. (A) (mm) | CSA (mm <sup>2</sup> ) | WEIGHT (kg) | PART NO.    |
|-----------------|-----------------|--------------------|------------------------|-------------|-------------|
| 4.2             | 200             | 7.0                | 6.0                    | 0.01        | CB200/6/7   |
| 4.2             | 400             | 7.0                | 6.0                    | 0.02        | CB400/6/7   |
| 5.4             | 200             | 7.0                | 10                     | 0.02        | CB200/10/7  |
| 5.4             | 400             | 7.0                | 10                     | 0.04        | CB400/10/7  |
| 7.0             | 200             | 9.0                | 16                     | 0.03        | CB200/16/9  |
| 7.0             | 400             | 9.0                | 16                     | 0.06        | CB400/16/9  |
| 8.5             | 200             | 11                 | 25                     | 0.05        | CB200/25/11 |
| 8.5             | 400             | 11                 | 25                     | 0.10        | CB400/25/11 |
| 11.5            | 200             | 11                 | 50                     | 0.10        | CB200/50/11 |
| 11.5            | 400             | 11                 | 50                     | 0.20        | CB400/50/11 |
| 14.5            | 200             | 13                 | 70                     | 0.13        | CB200/70/13 |
| 14.5            | 400             | 13                 | 70                     | 0.25        | CB400/70/13 |
| 16.0            | 200             | 13                 | 95                     | 0.19        | CB200/95/13 |
| 16.0            | 400             | 13                 | 95                     | 0.37        | CB400/95/13 |

**Material:** Copper


**Standard:** BS:EN 13602

**FIXINGS**  
Use M8 or M10 stainless steel nuts, bolts and washers

**SEE FIXINGS SECTION PAGE FIX:2**

**OTHER SIZES, MATERIALS, HOLE SIZES ETC. AVAILABLE ON REQUEST.**

### Flexible Circular Copper Braid Bonds (Tinned)



**Flexible Circular Copper Braid Bonds (Tinned)** are terminated with cable lugs at each end. Use to bond gates, doors, fences etc.

| BRAID DIA. (mm) | LENGTH (B) (mm) | HOLE DIA. (A) (mm) | CSA (mm <sup>2</sup> ) | WEIGHT (kg) | PART NO.     |
|-----------------|-----------------|--------------------|------------------------|-------------|--------------|
| 4.2             | 200             | 7.0                | 6.0                    | 0.01        | CBT200/6/7   |
| 4.2             | 400             | 7.0                | 6.0                    | 0.02        | CBT400/6/7   |
| 5.4             | 200             | 7.0                | 10                     | 0.02        | CBT200/10/7  |
| 5.4             | 400             | 7.0                | 10                     | 0.04        | CBT400/10/7  |
| 7.0             | 200             | 9.0                | 16                     | 0.03        | CBT200/16/9  |
| 7.0             | 400             | 9.0                | 16                     | 0.06        | CBT400/16/9  |
| 8.5             | 200             | 11                 | 25                     | 0.05        | CBT200/25/11 |
| 8.5             | 400             | 11                 | 25                     | 0.10        | CBT400/25/11 |
| 11.5            | 200             | 11                 | 50                     | 0.10        | CBT200/50/11 |
| 11.5            | 400             | 11                 | 50                     | 0.20        | CBT400/50/11 |
| 14.5            | 200             | 13                 | 70                     | 0.13        | CBT200/70/13 |
| 14.5            | 400             | 13                 | 70                     | 0.25        | CBT400/70/13 |
| 16.0            | 200             | 13                 | 95                     | 0.19        | CBT200/95/13 |
| 16.0            | 400             | 13                 | 95                     | 0.37        | CBT400/95/13 |

**Material:** Tinned Copper

**Standard:** BS:EN 13602

**FIXINGS**  
Use M8 or M10 stainless steel nuts, bolts and washers

**SEE FIXINGS SECTION PAGE FIX:2**

**OTHER SIZES, MATERIALS, HOLE SIZES ETC. AVAILABLE ON REQUEST.**