

Stranded Copper Cable (Green/yellow PVC covered)

Kingsmill **Stranded Copper Cable (Green/yellow PVC covered)** for use as earth continuity conductors, equipment tails etc.

STRANDING No./DIA (mm)**	NOMINAL DIAMETER (mm)	CSA (mm ²)	WEIGHT (kg/m)	PART NO.
7 / 1.70	7.10	16	0.15	CCGY016
7 / 2.14	8.90	25	0.23	CCGY025
7 / 2.52	9.95	35	0.32	CCGY035
19 / 1.78	11.70	50	0.43	CCGY050
19 / 2.14	13.35	70	0.62	CCGY070
19 / 2.52	15.60	95	0.86	CCGY095
37 / 2.03	17.20	120	1.09	CCGY120
37 / 2.25	19.10	150	1.33	CCGY150
37 / 2.52	21.30	185	1.67	CCGY185
61 / 2.25	24.30	240	2.20	CCGY240
61 / 2.52	27.05	300	2.76	CCGY300
61 / 2.85	30.35	400	3.53	CCGY400

Material: Soft drawn stranded copper cable **Stranding may vary

Standard: BS:EN 60228 (conductor), BS 6746C (PVC colour)

Temp range: 0°C to 70°C

Such conductors are generally referred to in the industry as 6491X, voltage rating 450/750V (designated suitable 600/1000V).

