


Tinned Copper Cable Lugs



Compression Tube Lugs are manufactured from high conductive electrolytic copper and are tin plated for excellent corrosion resistance. We also supply **Compression Tube Lugs** complete with two stud holes.

CABLE (mm ²)	STUD (X) (mm)	WEIGHT (kg)	PART NO.
16	6	0.01	LTC16,06
16	8	0.01	LTC16,08
16	10	0.01	LTC16,10
16	12	0.01	LTC16,12
25	6	0.01	LTC25,06
25	8	0.01	LTC25,08
25	10	0.01	LTC25,10
25	12	0.01	LTC25,12
35	6	0.01	LTC35,06
35	8	0.01	LTC35,08
35	10	0.01	LTC35,10
35	12	0.01	LTC35,12
50	6	0.02	LTC50,06
50	8	0.02	LTC50,08
50	10	0.02	LTC50,10
50	12	0.02	LTC50,12

Material: Tinned copper
Standard: BS 7430

CABLE (mm ²)	STUD (X) (mm)	WEIGHT (kg)	PART NO.
70	8	0.04	LTC70,08
70	10	0.04	LTC70,10
70	12	0.04	LTC70,12
70	14	0.04	LTC70,14
70	16	0.04	LTC70,16
95	8	0.06	LTC95,08
95	10	0.06	LTC95,10
95	12	0.06	LTC95,12
95	14	0.06	LTC95,14
95	16	0.06	LTC95,16
120	10	0.06	LTC120,10
120	12	0.06	LTC120,12
120	14	0.06	LTC120,14
120	16	0.06	LTC120,16
150	10	0.09	LTC150,10
150	12	0.09	LTC150,12

OTHER SIZES ARE AVAILABLE ON REQUEST

CABLE (mm ²)	STUD (X) (mm)	WEIGHT (kg)	PART NO.
150	14	0.09	LTC150,14
150	16	0.09	LTC150,16
185	12	0.11	LTC185,12
185	14	0.11	LTC185,14
185	16	0.11	LTC185,16
240	12	0.14	LTC240,12
240	14	0.14	LTC240,14
240	16	0.14	LTC240,16
300	12	0.17	LTC300,12
300	14	0.17	LTC300,14
300	16	0.17	LTC300,16
400	12	0.21	LTC400,12
400	14	0.21	LTC400,14
400	16	0.21	LTC400,16