

Insulated Lightning Conductor Wall Mounted Interception Mast - 3m to 7m high



OVERALL HEIGHT (A) (mm)	AIR TERMINAL HEIGHT (B) (mm)	SUPPORTING MAST HEIGHT (C) (mm)	WEIGHT (kg)	PART NO.
3000	500	1000	2.70	KM96223005
4000	1000	1500	3.70	KM96224005
5000	1000	2500	5.10	KM96225005
6000	1000	3500	6.50	KM96226005
7000	1000	4500	7.70	KM96227005

The **Wall Mounted Interception Mast** is supplied in three sections:

- Stainless steel **Supporting Mast**
- 1500mm glass fibre **Insulation Section**
- Aluminium **Air Terminal**

When mounting against a wall or flat vertical structure, it is recommended that a minimum of 1000mm of the mast assembly is below the top of the wall/vertical surface.

It is recommended that two **Mast Holders** are used for each mast, spaced at a distance of 800mm apart.

The mast can be fixed to the wall using two of our KM96000102 **Wall Mounted Brackets** (page AT:41).

Alternatively, when fixing to handrails or tubular structures, the mast can be secured using two each of the following items:

- Mast Holder KM96000701 (page AT:44)
- Pipe/Handrail Brackets (suitably sized) (pages AT:47 - 48)

Material: Aluminium Air Terminal
GRP Insulation Section
Stainless Steel Supporting Mast



FIXINGS

KM96000202 (page AT:41) for fixing to the wall
KM96000401 (page AT:41) for fixing to pipes/handrails

