

STRIKEBAND Copper Covered Aluminium

STRIKEBAND Copper Covered Aluminium is sold in the specified coil length only. Copper thickness is 15% by volume, giving a radial thickness of 0.25mm.

DESCRIPTION	DIMENSION (mm)	COIL LENGTH (m)	WEIGHT (per m) (kg)	PART NO.
Copper/aluminium bimetallic conductor	25 x 3	74	0.27	CCAT2530

Material: 99.9% purity copper and 99.7% purity aluminium



Copper Tape (Bare)

Kingsmill **Copper Tape** is embossed 'Kingsmill (UK)' for identification and is manufactured from high conductivity annealed copper.

All **Bare Copper Tape** sold in the specified coil lengths only. However, **CTBA2530** can be cut to desired length. Please speak to the sales office for further details referencing part no. **CTBA2530/DRUM**.

CONDUCTOR SIZE (X x Y) (mm)	CSA (mm ²)	COIL SIZE (m)	WEIGHT (kg/m)	PART NO.
12.5 x 1.5	18.75	100	0.17	CTBA1215
12.5 x 3	37.5	100	0.33	CTBA1230
20 x 1.5	30	100	0.27	CTBA2015
20 x 3	60	100	0.53	CTBA2030
25 x 1.5	37.5	100	0.33	CTBA2515
25 x 3	75	25	0.67	CTBA2530/25
25 x 3	75	50	0.67	CTBA2530
25 x 4	100	50	0.89	CTBA2540
25 x 6	150	40	1.34	CTBA2560
30 x 2	60	50	0.53	CTBA3020
30 x 3	90	50	0.80	CTBA3030
30 x 4	120	40	1.07	CTBA3040
30 x 5	150	40	1.33	CTBA3050
31 x 3	93	50	0.83	CTBA3130
31 x 6	186	30	1.65	CTBA3160
38 x 3	114	50	1.01	CTBA3830
38 x 5	190	30	1.69	CTBA3850
38 x 6	228	25	2.03	CTBA3860
40 x 3	120	40	1.06	CTBA4030
40 x 4	160	30	1.42	CTBA4040
40 x 5	200	25	1.78	CTBA4050
40 x 6	240	25	2.13	CTBA4060
50 x 3	150	40	1.33	CTBA5030
50 x 4	200	30	1.78	CTBA5040
50 x 5	250	20	2.22	CTBA5050
50 x 6	300	20	2.68	CTBA5060

Material: Copper to BS:EN 13601 (formerly BS 1432)

Standard: BS:EN 62561-2 : 2012

